



An ISO 9001:2015 Company

CIRCUIT BREAKER TIMER

Model : KM-CBT-01 / KM-CBT-02

NEW



KM-CBT-01

FEATURES:

- 3 / 4 pole measurement simultaneously.
- C, O, C-O with bounce time measurement.
- Timer range: 0 ~ 9999.9mSec.
- Resolution: 0.1ms
- Built-in Thermal Printer (KM-CBT-02)
- Internal memory for 100 records (KM-CBT-02)
- USB interface for data transfer & report (KM-CBT-02)



KM-CBT-02

TECHNICAL SPECIFICATIONS:

Specifications	KM-CBT-01	KM-CBT-02
Number of Phases	3 / 4 Phases	3 / 4 Phases
Breaks pe Phase	1	1
Timer Range	0.1ms ~ 9999.9ms	0.1ms ~ 9999.9ms
Resolution	0.1ms	0.1ms
Accuracy	0.05% $\pm$ 1 digit	0.05% $\pm$ 1 digit
Modes of Operation	C, O, C-O with bounce	C, O, C-O with bounce
Display	4 Line backlight LCD display	4 Line backlight LCD display
PC interface	NO	USB
Memory	NO	100 Test Results
Printer	NO	inbuilt Thermal Printer
Mains	90V to 250V $\pm$ 10%, 50 / 60Hz	90V to 250V $\pm$ 10%, 50 / 60Hz
Battery	NO	Lead Acid 12V, 7.6Ah

STANDARD ACCESSORIES :

- Test Lead Set - 10Meter long
- Control Cable - 5Meter long
- Earthing Cable- 5Meter long
- Mains Cord
- Thermal Paper Roll - 1No (KM-CBT-02)
- Software CD & USB Cable (KM-CBT-02)
- Instruction Manual

All Specifications are subject to change without prior notice.



An ISO 9001:2015 Company

Shop No. 18, 1st floor, CIDCO Shopping Complex, Plot No 9, Sector-7, Rajiv Gandhi Marg, Sanpada, Navimumbai-400705. INDIA.
Email : sales@kusam-meco.co.in
Tel.: 022-27754546 / 27750662 / 27750292
Web : www.kusamelectrical.com