

MOISTURE METER

SPECIFICATIONS :

- Parameters : % material moisture content, temperature,
- Accuracy : Conductivity measurement : $\pm 2\%$ Temperature : $\pm 1^{\circ}\text{C}$
- Resolution : 0.1%, 0.1 $^{\circ}\text{C}$, 0.1 $^{\circ}\text{F}$
- Measurement range : 0.0% ~ 95.7%, -10 ~ + 50 $^{\circ}\text{C}$
- Digital display : 3 digits.
- Measurement selection :
 - Material 1 : 8.9 ~ 95.7% (Hard wood such as Beech, Spruce, Larch, Birch, Cherry, Walnut and so on)
 - Material 2 : 7.1 ~ 80.0% (Soft wood such as Oak, Pine, Maple, Ash-tree, Douglas fir, Meranti and so on.)
 - Material 3 : 1.0 ~ 2.5% (Cement or Concrete plane, Plaster produce.)
 - Material 4 : 0.0 ~ 3.3% (Anhydrite plane)
 - Material 5 : 0.7 ~ 3.8% (Cement mortar)
 - Material 6 : 0.5 ~ 7.4% (Lime mortar)
 - Material 7 : 0.0 ~ 23.4% (Bricks)

Model KM 8040**Preliminary Data**

All Specifications are subject to change without prior notice