DIGITAL SOUND LEVEL METER

KM 8080 is the most popular sound level meter that gives the possibilities of measuring the level of noise with hindication of digital display with analog graph. The Auto & Manual ranging provides wide possibilities for indication and data updating. It is also capable of measuring four (4) ranges from 30 ~ 120dB and features 0.1 dB resolution. It allows you to select fast response times with 0.25S and the auto - power off function save you the battery even if you forget to shut off the instrument. with KM 8080, you can easily monitor the sound levels from traffic noise, alarm systems and workplace machinery! Each of our sound level meters are high quality, innovative instruments designed specifically to address the needs of todays safety professionals. with our reputation for quality products and high level technical service, KM 8080 is your solution for sound level meter.

FEATURES :

- Standard applied : IEC651 Type2, ANSI S1.4 Type 2
- Frequency range : 31.5Hz ~ 8KHz
- Measuring range : 30db ~ 120db
- Frequency weighting : A
- Digital display : 4 digit
- Resolution : 0.1dB.
- Accuracy : 1.5dB (under 94dB)
- Four ranges : 30 ~ 60, 50 ~ 80, 70 ~ 100, 90 ~ 120dB
- Time responses : Analog bar : 0.25 S; Digital : 0.75 S
- Operating Temperature : 0 ~ 40 °C

ACCESSORIES :

User's Manual, DC 1.5V AAA x 3 Batteries, Wrist Strap & Carrying case.

- Operating humidity : 10 to 90% RH
- Auto and manual range selectable
- Analog bar indicator.
- Range display.

All Specifications are subject to change without prior notice

- · Auto power off.
- Software calibration.
- Low battery indication.
- Sound OVER or UNDER display.
- Power Supply : 1.5V AAAx3



G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA. Sales Direct.: 022 -2 4156638, Tel.: 022-241224540, 24181649, Fax: 022 - 24149659 Email: kusam_meco@vsnl.net, Website : www.kusamelectrical.com

Navin.com/D.drive/sandeep gupta/New catlog Dec 2011/KM-8080.cdr





KUSAM-MECO

An ISO 9001:2008 Company