

KUSAM-MECO

An ISO 9001:2008 Company

® CFM/CMM THERMO-ANEMOMETER**Model KM 910**

Anemometer is mainly used in electric power, iron and steel, petrochemicals, energy and other industries.

GENERAL SPECIFICATIONS :**AIR VELOCITY**

Range	Resolution	Accuracy
0.40 ~ 30.00 m/s	0.01 m/s	± (3% + 0.20 m/s)
1.4 ~ 108.0 km/h	0.1 km/h	± (3% + 0.8 km/hr)
80 ~ 5900 ft/min	1 ft/min	± (3% + 40 ft/m)
0.9 ~ 67.0 mph	0.1 mph	± (3% + 0.4 MPH)
0.8 ~ 58.0 knots	0.1 knots	± (3% + 0.4 knots)

AIR FLOW (CMM / CFM)

Range	Resolution	AREA
0 ~ 9999 m ³ /min	1	0 ~ 9.999m ²
0 ~ 9999 ft ³ /min	1	0 ~ 9.999ft ²

AIR TEMPERATURE

Range	Resolution	Accuracy
14~140°F (-10 ~ 60°C)	0.1°F / °C	4.0°F (2.0°C)

- **Operating Voltage** : 9V
- **Dimension** : 202 x 85 x 48mm
- **Weight** : Approx. 240g
- **Accessories** : Battery, User Manual & Carrying Case.



Preliminary Data

All Specifications are subject to change without prior notice.

KUSAM-MECO®

An ISO 9001:2008 Company

G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA.
Sales Direct.: 022-24156638, **Tel. :** 022-24124540, 24181649, **Fax :** 022-24149659
Email : kusam_meco@vsnl.net, **Website :** www.kusamelectrical.com