



An ISO 9001:2008 Company

ELECTROMAGNETIC RADIATION TESTER

Model KM 196

GENERAL SPECIFICATIONS :

- **Unit** : Electric Field : V/m; Magnetic Field : μT
- **Precision** : Electric Field : 1V/m; Magnetic Field : 0.01 μT
- **Range** : Electric Field : 1V/m ~ 1999V/m.
Magnetic Field : 0.01 μT ~ 19.99 μT
- **Alarm Threshold** : Electric Field : 40V/m, Magnetic Field : 0.4 μT
- **Reading Display** : 3½ Digit Digital LCD display with Backlight.
- **Frequency Range** : 5Hz ~ 3500MHZ
- **Sampling Time** : About 0.4 second.
- **Measuring Mode** : Dual Mode
- **Overload Alert** : "1" appears on LCD
- Sound & Light Alarm
- Data Hold function.
- Auto Power Off.
- Average & Peak measurement.
- Low Battery Indication.
- **Operating Temperature & Humidity** : 0°C ~ 50°C; below 80%RH.
- **Power Supply** : 9V Battery.
- **Dimension** : 63.6 x 31 x 125.8mm
- **Weight** : Approx. 146g.
- **Accessories** : Battery, User Manual & Carrying Case.



Preliminary Data

All Specifications are subject to change without prior notice.



An ISO 9001:2008 Company

G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA.
Sales Direct.: 022-24156638, **Tel. :** 022-24124540, 24181649, **Fax :** 022-24149659
Email : kusam_meco@vsnl.net, **Website :** www.kusamelectrical.com