



An ISO 9001:2008 Company

DIGITAL EARTH RESISTANCE Model KM 2030

GENERAL SPECIFICATIONS :

- Display : 3½ Digit LCD display.
- Ground resistance measurements from 0 ~ 01Ω to 2000Ω with 0.01Ω resolution.
- **Earth Resistance** : 20Ω / 200Ω / 2000Ω
- **Accuracy** : 20Ω : ± (2% + 0.1Ω);
200Ω / 2000Ω : ± (2% + 3)
- **Earth Voltage** : 0 ~ 30V
- **Accuracy** : ± (3% + 5)
- **Resolution** : 0.01Ω
- Working LED Indicator.
- Data Hold Function.
- **Response Time** :
Measure earth resistance, about 5 seconds.
Measure Earth Voltage, about 2 seconds.
- **Withstand Voltage** : AC 1500V
- Low battery indication.
- **Power** : AA 1.5V X 6 & 12V x 1 Battery.
- **Weight** : approx. 680g.
- **Dimension** : 150(L) x 100(W) x 70(D) mm.
- **Standard Accessories** : Test Wires, Earth wire, Auxiliary Earth Bars, Instruction Manual, Battery & Carrying Case.



Preliminary Data

All Specifications are subject to change without prior notice



An ISO 9001:2008 Company

G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA.
Sales Direct.: 022 -24156638, **Tel. :** 022-24124540, 24181649, **Fax :** 022 - 24149659
Email : kusam_meco@vsnl.net **Website :** www.kusamelectrical.com