



An ISO 9001:2015 Company

DIGITAL LUX METER MODEL - KM 8051 MK-1

FEATURES :

- **Display** : 3½ Digit 2000 counts for Illuminance & 3 digits for temperature.
- **Measuring Function** : Illumination & temperature, difference value, max value, min value of illumination.
- Back light & Data Holding function
- Switch between illumination & Temperature unit.
- **Temperature Probe** : NTC Thermistor
- **Measurement Range** : 0 ~ 200,000 Lux (4 ranges)
0~199.9 / 200~1999.9 / 2000~19999.9 / 20000~200000Lux
- **Accuracy** : ± 3% rdg (below 10000Lux)
± 4% rdg (Above 10000Lux)
- **Temperature Measuring Range** : -9.9°C ~ 49.9°C
- **Accuracy** : ± 1.0°C
- **Units**: Lux/°C, Lux/°F, FC/°C, FC/°F
- **Maximum No. of Data Group in Manual Storage** : 67 data.
- **Maximum No. of Data Group in Automatic Storage** : 1000 data.
- **Sample Rate** : 2 time / sec.
- **Operating Temperature & Humidity** : 0 ~ 40°C; 10~90%RH
- **Storage Temperature & Humidity** : -10 ~ 50°C; 10~90%RH
- Setting of automatic power off.
- **Power supply** : 1.5V x 3 AAA Battery
- **Weight** : Approx. 280g. (including battery)



Preliminary Data

ACCESSORIES :

Users Manual, Battery & Carrying Case.

All specifications are subject to change without prior notice.



An ISO 9001:2015 Company

G-17, Bharat Industrial Estate, T. J. Road, Sewree (W), Mumbai - 400 015. INDIA.
Sales Direct.: 022-24156638, 27754546 Tel. : 24124540, 24181649, 27750662, 27750292
Email : sales@kusam-meco.co.in Web: www.kusamelectrical.com