



KUSAM-MECO Digital Tachometers use latest technology for accurate measurements. It has Exclusive one chip of Microcomputer LSI Circuit, It is housed in tough ABS case & has ergonomic design for easy holding in the hand.

SPECIFICATIONS :

Display	5 digits, 18mm (0.7") LCD White Backlight display
Sampling Time	0.8 sec. (Over 60 RPM)
Test Range	Autoranging
Range I	Photo mode: 2.5 to 99999 RPM
Range II	Contact Mode : 0.5 to 19999 RPM
	Surface speed 0.05 to 1999.99m/min.
Accuracy	± (0.05% + 1dgt)
Resolution	Photo rotation speed: 0.1 RPM(0.5 to 999.9RPM)
	1 RPM (over 1000RPM)
	Contact rotation speed: 0.1 RPM(0.5 to 999.9 RPM)
	1 RPM over 1000 RPM
	Surface speed:0.01m/min(0.05 to 99.99m/min)
	0.1m/min(over100m/min)
Memory	Max value, Min value & Last value automatically stored in memory & save 96 set of continuous data.
Detecting Distance	50 to 500mm (photo mode)
Operating Temperature	0 - 50°C
Operating Humidity	Less than 80% RH
Power Supply	3 x 1.5 V AA Size Battery
Dimension (L X W X D)	155 x 70 x 35mm (without contact tacho part)
Weight	235 gms including batteries
Accessories	User Manual, Carrying case, Surface speed Test Wheel, RPM adapter(cone), RPM adapter (funnel) & 2pcs of Reflecting Tape (350mm).

All Specifications are subject to change without prior notice.